



LLIFE-2PRO-SMS-1200-BLK

Bare Emergency Batten 1200mm ,Twin Lifelight Pro,
Surface Mount, L10 Nanophosphate, Clevertest Plus, Black



PRODUCT INFORMATION

Part Number	LLIFE-2PRO-SMS-1200-BLK
MIC	AUT01310570001
Description	Bare Emergency Batten 1200mm ,Twin Lifelight Pro, Surface Mount, L10 Nanophosphate, Clevertest Plus, Black
Construction	Powder Coated Metal Enclosure PC/ABS Heads
Mounting	Surface Mount, can also be Chain Suspended
Dimensions L x W x H	1220mm x 110mm x 50mm
Weight	1.5kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not Activated by Default)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Twin Dual LED (Lifetime Warranty on the Lamp Head and Loom Assembly)
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.8W (Standby), 5.4W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D160 C ₉₀ =D160
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
1100867	LED Head Assembly x 2
AUM01370120001 LLIFE-PRO-CKIT-NP	Driver Pack

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.