

## CLEVERTRONICS L10 OPTIMUM LIFELIGHT PRO SPOTLIGHT EMERGENCY (ZONENWORKS XT HIVE), BLACK



### PRODUCT INFORMATION

Catalogue Number	LLIFE-PRO-HV-SPOT-BLK
MIC	AUT01810070001
Description	L10 Lifelight PRO, High Performance, Spotlight Style Emergency Light, Black
Mounting	Lamp head assembly - Ceiling or wall mount with adjustable lamp head direction Control gear and battery – Remote mounted and connected via the standard 1m length of cable (same as the standard Lifelight PRO)
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack), 105mm 100mm x 60mm (Lamp Head and Swivel)
Operating Mode	Non-Maintained
Testing System	Zoneworks XT HIVE (RF)
Ballast	N/A
Charging Method	Intelligent current limited constant voltage charger
Lamps(s)	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V 50Hz
Power Consumption	0.4W (Standby), 4.7W (Max)
IP Rating	IP20
Impact Rating	N/A
Operating Temperature	1° to 40°C (Ambient)
AS/NZ2293 Classification	C <sub>0</sub> =D80 C <sub>90</sub> =D80

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1100841	Lifelight Pro Head Assbly,Rnd,Large+Ring,Blk,Gen 2
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
LLIFE-PRO-CKIT	Lifelight Pro, Control Only, L10
8003191	PCA: RF Node CT10678-A9 Int Antenna LLPro

*The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order*