

## **LLIFE-PRO-SPOT**

## CLEVERTRONICS L10 OPTIMUM LIFELIGHT PRO SPOTLIGHT EMERGENCY



PRODUCT INFORMATION	
Part Number	LLIFE-PRO-SPOT
MIC	AUT01310170001
Description	L10 Lifelight PRO, High Performance, Spotlight Style Emergency Light
Mounting	Lamp head assembly - Ceiling or wall mount with adjustable lamp head direction Control gear and battery – Remote mounted and connected via the standard 1m length of cable (same as the standard Lifelight PRO)
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack), 105mm 100mm x 60mm (Lamp Head and Swivel)
Operating Mode	Non-Maintained
Testing System	Manual Test Switch
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage charger
Lamp(s)	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4W (Standby), 2.7W (max during 16 hour charge)
IP Rating	IP20
Operating Temperature	1°C to 40°C
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530230	Battery
110868	Emergency LED Head Assembly
AUM01370040001 LLIFE-PRO-CKIT	Emergency Driver CKIT

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

