



LLIFEM-PRO-HV-BLK

CLEVERTRONICS L10 MAINTAINED LIFELIGHT PRO
RECESSED EMERGENCY - BLACK



PRODUCT INFORMATION

| | |
|--------------------------|---|
| Part Number | LLIFEM-PRO-HV-BLK |
| MIC | AUT01810250001 |
| Description | L10 Optimum Maintained Lifelight PRO, Recessed Emergency Light, Black |
| Mounting | Recessed Ceiling |
| Dimensions L x W x H | 232mm x 40mm x 40mm (Control Pack) 60mm Head Diameter (95mm with adaptor plate) |
| Ceiling hole cut-out | 51mm, 85mm (with adaptor plate) |
| Minimum ceiling depth | 200mm, 120mm (with adaptor plate) |
| Operating Mode | Maintained (LEDs permanently ON at 250mA - 182lm, with no switch control) Emergency mode (LEDs running at 550mA - 336lm) |
| Testing System | Zoneworks XT HIVE (RF) |
| Battery | Lithium Nanophosphate, 3.3V 5000mAh |
| Charging Method | Intelligent current limited constant voltage charger |
| Lamp(s) | 2 x 3W LED (Lifetime warranty on the lamp head and loom assembly) |
| Operating Voltage | 240V 50Hz |
| Power Consumption | 2.7W (Standby), 5W (Max during 16 hour charge) |
| IP Rating | IP20 |
| Operating Temperature | 1° to 40°C (Ambient) |
| AS2293 Classification | C0=D80 C90=D80 |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|--------------------------------------|--|
| 1530230 | Battery: 3.3V 5Ah.Li-ion, 200mm lead with Bracket |
| 1100871 | Lifelight Pro Head Assbly,Rnd,Lge+Ring,LT,Blk,Gen2 |
| AUM01870180001 LLIFEM-PRO-CKIT-HV | Lifelight Pro, Control Only, MNT, HV, L10 |
| 8003191 | PCA: RF Node CT10678-A12 Int Antenna LLPro |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order