

CLEVERTRONICS L10 MAINTAINED LIFELIGHT PRO RECESSED EMERGENCY (ZONWORKS XT HIVE)



PRODUCT INFORMATION

Catalogue Number	LLIFEM-PRO-SA-HV
MIC	AUT01810170001
Description	L10 Lithium Nanophosphate LifeLight PRO, high performance, recessed Emergency Light maintained, (switched active on/off control of LED's)
Construction	PC/ABS Head
Mounting	Recessed Ceiling
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) , 60mm Head Diameter (95mm with adaptor plate)
Ceiling Hole Cut-Out	51mm, 85mm (with adaptor plate)
Minimum Ceiling Depth	200mm, 120mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Maintained (LEDs permanently ON at 250mA - 182lm) Emergency mode (LEDs running at 550mA - 336lm)
Testing System	Zoneworks XTHIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	2.7 Watts (Standby) 5 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D80 C ₉₀ =D80

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
AUM01870010001 LLIFE-PRO-CKIT-HV	Lifelight Pro, Control Only, HV, L10 (incl. Hive node)
1100868	Lifelight Pro Head Assbly,Rnd,Large+Ring, LT,Gen 2
8003191	PCA: RF Node CT10678-A9 Int Antenna LLPro

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order