



LLIFEM-PRO-SA

CLEVERTRONICS L10 MAINTAINED LIFELIGHT PRO RECESSED EMERGENCY



PRODUCT INFORMATION

Part Number	LLIFEM-PRO-SA
MIC	AUT01310430001
Description	L10 Lithium Nanophosphate LifeLight PRO, high performance, recessed Emergency Light maintained, (switched active on/off control of LED's), Enabled with Clevertest Plus
Construction	PC/ABS Head
Mounting	Recessed Ceiling
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) , 60mm Head Diameter (95mm with adaptor plate)
Ceiling Cut-Out	51mm, 85mm (with adaptor plate)
Minimum Ceiling Depth	200mm, 120mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Maintained (LEDs permanently ON at 250mA - 182lm) Emergency mode (LEDs running at 550mA - 336lm)
Testing System	Enabled with Clevertest Plus
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	2.4 Watts (Standby) 4.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
AUM01370320001 LLIFEM-PRO-SA-CKIT	Emergency Driver Pack
1100868	Emergency LED Head Assembly

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.