



LLIFEM-PRO-SM-DALI

CLEVERTRONICS L10 LIFELIGHT PRO EMERGENCY LUMINAIRE SURFACE MOUNT



PRODUCT INFORMATION

Part Number	LLIFEM-PRO-SM-DALI
MIC	AUT01210600002
Description	L10 Optimum Lifelight PRO, High Performance, Surface Mounted Maintained Emergency Light
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.7kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	2.7W (Standby) 5.0W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530231	Battery
8003081	Emergency LED Head Assembly
8003501	Driver
8003060	DALI Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.