



LUBPRO-DALI

CLEVERTRONICS L10 ULTRABLADE PRO



PRODUCT INFORMATION	
Part Number	LUBPRO-DALI
MIC	AUA01211000003
Description	L10 Lithium Nanophosphate Ultrablade Pro Blade Exit
Construction	PC/ABS Body with PC Diffuser
Mounting	Recessed Ceiling Mount
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Cut-Out	350mm x 48mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate 3.3V 2.5Ah
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All Pictograph Directional Inserts Included in the Box
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	4.2W (Lamps ON Max), 3.8W (Lamps ON Standby)
Inrush Current (Max)	13.08A<84µs
Earth Leakage	0.331mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E6.3, C90=E6.3
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530050	Battery
8002178	Emergency LED Panel
AUM01270340003 LUBPRO-CKIT-DALI	Emergency Driver Pack
8003060	DALI Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.