



LUBPRO-SM-TH-DALI-RL

CLEVERTRONICS L10 ULTRABLADE PRO SURFACE MOUNT EXIT, THEATRE (DALI)



PRODUCT INFORMATION	
Part Number	LUBPRO-SM-TH-DALI-RL
MIC	AUA01260760002
Description	L10 Optimum Ultrablade Pro Surface Mount LED Blade Exit, Theatre
Construction	PC/ABS Body with PC Diffuser
Mounting	Wall or Ceiling Mounted, Single-Sided
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.0kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate 3.3V 2.5Ah
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre Mask, Running Man, Arrow Left
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530030	Battery
8002178	LED Strip
8003135	Driver
8003060	DALI Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order