




LVELED-WM-DALI

CLEVERTRONICS L10 HIGH IMPACT SECURITY EXIT, WALL MOUNTED



Tamperproof screws

PRODUCT INFORMATION

Part Number	LVELED-WM-DALI
MIC	AUA01230030003
Description	L10 Optimum Cleverfit PRO Exit in vandal resistant case, wall mounted
Construction	Strong Steel Body with PC Diffusers
Mounting	Single Sided Wall Mount
Dimensions L x W x H	425mm x 100mm x 270mm
Weight	6.6kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 3.9 Watts (Max)
IP Rating	IP20
Impact Rating	IK12
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D3.2 C ₉₀ =E8
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	BATTERY:L10 3.3V 2.5AH 260mm lead,noBRKT
8002710	LED:PCA:DurisLED Strip Clvrft Pro CT10276-D3
8003152	DRIVER:PCA:CCF-Pro #CT10622 6C40 DReg, Hive
8003060	PCA: DALI Node #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.