

CLEVERTRONICS L10 ARGONAUT 600MM VANDAL BATTEN



PRODUCT INFORMATION

Part Number	LVP2LEDM-P-DD-DALI
MIC	AUB01230050001
Description	L10 Lithium Nanophosphate 600mm Argonaut LED Vandal Batten with Battery Pod with DALI Driver
Construction	Pressure die-cast, low copper aluminium alloy body with powder coat paint finish Removable gear tray and replaceable LED modules
Mounting	Surface mount
Dimensions L x W x H	790mm x 140mm x 120mm (including battery POD)
Weight	3.2kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 6.6V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Opal, Impact Resistant Polycarbonate with Secure Access Screws, LSZH
Driver / Ballast	Tridonic LC 50W 350-1050mA, ONEFORALL
Lamp(s)	1 x LED module, 4000K natural white, 100,000h [L80/ B20, Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	> 0.9
Total lumen output	2529 lm @ 109lm/W
Power Consumption	27W (MAX Charge - Lamp ON), 23W (Standby Lamp ON), 1W (Standby Lamp OFF)
IP Rating	IP66
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D32
Impact Rating	IK10

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530260	BATT:L10 6.6V 2500mAh.200mm lead.SBS.
1330056	LED Driver - LCA 50w 350-1050mA,ONEFORALL
8002699	PCA: LED Strip 5P8S, ALS-50-840-3-01-A
AUM01270030102 LCPLED-48V95C-CKIT-DALI	LED Power Pack, 48V 95mA, 6.6V 2.5Ah,Dali Reg, L10 (incl. DALI Node)
8003065	PCA: DALI Node #CT10629-Ax Horizontal

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order