



LVP2LEDM-P-DD

CLEVERTRONICS L10 VANDAL RESISTANT BATTEN WITH DALI DRIVER



PRODUCT INFORMATION

Part Number	LVP2LEDM-P-DD
MIC	AUB01330090001
Description	L10 Lithium Nanophosphate 600mm Argonaut LED Vandal Batten with Battery Pod with DALI Driver
Construction	Pressure die-cast, low copper aluminium alloy body with powder coat paint finish Removable gear tray and replaceable LED modules
Mounting	Surface Mount
Dimensions L x W x H	1400mm x 140mm x 120mm
Weight	5.2kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled
Battery	Lithium Nanophosphate, 6.6V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Opal, Impact Resistant Polycarbonate with Secure Access Screws, LSZH
Driver / Ballast	Tridonic LC 50W 350-1050mA ONE4ALL
Lamp(s)	1 x LED module, 4000K natural white, 100,000h [L80/ B20, Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.9
Power Consumption	27W (MAX Charge - Lamp ON), 23W (Standby Lamp ON), 1W (Standby Lamp OFF)
Total Lumen Output	2529 lm @ 109lm/W
Operating Temperature	0°C to 40°C
IP Rating	IP66
Impact Rating	IK10
AS2293 Classification	C ₀ =D63 C ₉₀ =D32
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530260	Battery
1330056	240V Driver
8002699	Emergency LED Panel
AUM01370260001 LCPLED-38V120C-CKIT	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order