



## LVP4LEDM-P-DALI

CLEVERTRONICS Argonaut 1200mm Vandal Resistant Emergency Batten, L10, DALI Emergency



### PRODUCT INFORMATION

Part Number	LVP4LEDM-P-DALI
MIC	AUB01230010003
Description	Argonaut 1200mm Vandal Resistant Emergency Batten, L10, DALI Emergency
Construction	Pressure Die-cast, Low Copper Aluminium Alloy Body with Grey Powder Coat Paint Finish. Removable Gear Tray and Replaceable LED Modules.
Mounting	Surface Mount
Dimensions L x W x H	1400mm x 140mm x 120mm (Including Battery POD)
Weight	5.2kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 6.6V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Opal, Impact Resistant Polycarbonate with Secure Access Screws
Driver / Ballast	LED Driver - LC 50w 350-1050mA, 20-50V
Lamp(s)	LED strip module, 4000K, Ra>80 L70/B50 Ta 40°C; LM80 Report >60,000hr, Projected 184,000hr L80/B20 Ta 40°C; LM80 Report >60,000hr, Projected 100,000hr L90/B10 Ta 40°C; LM80 Report 43,000hr, Projected 43,000hr
Operating Voltage	220-240V~ 50Hz
Power Factor	0.85
Power Consumption	43.5W (MAX Charge Lamp ON), 39.7W (Standby Lamp ON), 1.2W (Standby Lamp OFF)
Inrush Current	20.21A<92µs
Earth Leakage	0.103mA
Total Lumen Output	5632lm @ 129.5lm/W (Based on Non-emergency Version)
Operating Temperature	0°C to 40°C
IP Rating	IP66
Impact Rating	IK10
AS2293 Classification	C0=D100 C90=50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.1
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530260	Battery
1330055	240V Driver
8002755	240V LED Panel
AUM01270540002 LCPLED-4W-CKIT-DALI-HBL	Emergency Driver Pack
8003065	Node - DALI

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order