



LVP4LEDM-P

CLEVERTRONICS L10 ARGONAUT VANDAL BATTEN



PRODUCT INFORMATION	
Part Number	LVP4LEDM-P
MIC	AUB01330030002
Description	L10 Optimum 4ft Argonaut LED Vandal Batten with Battery POD and LED Modules/Light Engines, Enabled with Clevertest Plus
Construction	Pressure Die-cast, Low Copper Aluminium Alloy Body with Grey Powder Coat Paint Finish. Removable Gear Tray and Replaceable LED Modules. Battery POD at one end. (Retains Through-Conduit/Wiring Capability even with the POD)
Mounting	Surface Mount
Dimensions L x W x H	1400mm x 140mm x 120mm (including battery POD)
Weight	5.2kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 6.6V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Opal, Impact Resistant Polycarbonate with Secure Access Screws, LSZH
Driver / Ballast	Tridonic LC 50W 350-1050mA
Lamp(s)	LED strip module, 4000K, Ra>80 L70/B50 Ta 40°C; LM80 Report >60,000hr, Projected 184,000hr L80/B20 Ta 40°C; LM80 Report >60,000hr, Projected 100,000hr L90/B10 Ta 40°C; LM80 Report 43,000hr, Projected 43,000hr
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Power Consumption	1.2W (Standby Off), 39.7W (Standby Off), 43.5W (Max)
Inrush Current (Max)	20.21
Earth Leakage	0.103mA
Total Lumen Output	5632 lm @ 129.5lm/W
Operating Temperature	0°C to 40°C
IP Rating	IP66
Impact Rating	IK10
AS2293 Classification	C ₀ =D100 C ₉₀ =D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530260	Battery
1330055	240V Driver
8002755	Emergency LED Panel
AUM01370610001 LCPLED-4W-CKIT-HBL	Emergency Driver