



LWELED-DALI

Weatherproof Exit, Surface Mount, L10 Nanophosphate, DALI Emergency, All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	LWELED-DALI
MIC	AUA01220120003
Description	Weatherproof Exit, Surface Mount, L10 Nanophosphate, DALI Emergency, All Pictograms, Single or Double Sided
Construction	Polycarbonate Clear Cover, Glass Reinforced Nylon PA66 Base
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	410mm x 100mm x 272mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	DALI registered
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.7W (Standby), 4.5 Watts (Max)
IP Rating	IP66/IP67
Impact Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D6.3, C ₉₀ =D5
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	BATTERY:L10 3.3V 2.5AH 390mm lead,noBRKT
8002710	LED: PCA: Duris LED Strip Cleverfit Pro CT10276-D3
8002358	DRIVER: PCA: CT10164-L6 6C43-83 DALIREG, HV
8003060	PCA: New DALI #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order