

## CLEVERTRONICS L10 WEATHERPROOF EXIT, THEATRE



### PRODUCT INFORMATION

Part Number	LWELED-TH-DALI-R
MIC	AUA01260630202
Description	L10 Lithium Nanophosphate weatherproof Emergency EXIT, Theatre
Construction	Polycarbonate clear cover, glass reinforced nylon PA66 base
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	410mm x 272mm x 100mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, Running man (Must specify diffuser combination)
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.7 Watts (Standby), 4.5 Watts (Max)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =N/A C <sub>90</sub> =N/A
Impact Rating	IK10
Viewing Distance	24m

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	BATTERY:L10 3.3V 2.5AH 390mm lead,noBRKT
8002330	PCA:LCFLED Driver. #CT10164-L4.
8002430	PCA:Duris P5 6 LED Strip.L10,#CT10166-D1
8003060	PCA: DALI Node #CT10629-Ax

