



## LWELED-TH-DS-RAOW

CLEVERTRONICS L10 WEATHERPROOF EXIT, THEATRE



### PRODUCT INFORMATION

Part Number	LWELED-TH-DS-RAOW
MIC	AUA01360320001
Description	L10 Lithium Nanophosphate weatherproof Emergency EXIT, Theatre, Enabled with Clevertest Plus
Construction	Polycarbonate clear cover, glass reinforced nylon PA66 base
Mounting	Wall, ceiling double-sided
Dimensions L x W x H	410mm x 272mm x 100mm
Operating Mode	Maintained
Testing System	Enabled with Clevertest Plus
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, Running man Arrow One Way
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.7 Watts (Standby), 4.5 Watts (Max)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	Battery
8002349	Driver
8002710	LED Strip

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.