



LWEPRO-FZR-HV

CLEVERTRONICS L10 CLEVERFIT PRO WEATHERPROOF EXIT FOR LOW TEMPERATURE APPLICATIONS



PRODUCT INFORMATION

Part Number	LWEPRO-FZR-HV
MIC	AUA01820250001
Description	L10 Optimum Cleverfit PRO Weatherproof Emergency EXIT for Low Temperature Applications
Construction	Exit: PC/ABS body with PC diffuser Enclosure: Polycarbonate Clear Cover, Glass reinforced Nylon PA66 Base
Mounting	Ceiling Mount - Double Sided / Wall Mount - Single Sided
Dimensions L x W x H	410mm x 100mm x 272mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x Duris E2 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.5 Watts (Max)
IP Rating	IP66/IP67
Operating Temperature	-25°C to 40°C
AS2293 Classification	C ₀ =D2.5 C ₉₀ =E4
Impact Rating	IK10
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	BATTERY:L10 3.3V 2.5AH 260mm lead, no Brkt
8002710	PCA:DurisLED Strip Clvrft Pro CT10276-D1
8002959	PCA:CCF-Pro #CT10142-L9 250mA Batt
8003191	PCA: RF Node CT10678-A12 Int Antenna LLPro

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order