

CLEVERTRONICS L10 WEATHERPROOF SURFACE MOUNT WITH TWIN LIFELIGHT PRO PODS



PRODUCT INFORMATION

Part Number	LWP2LIFE-PRO-WPPOD-DALI
MIC	AUT01220100202
Description	L10 Lithium Nanophosphate Lifelight Pro, high performance, IP65 surface mounted Emergency Light with twin rotatable LED Pods
Construction	Polycarbonate
Mounting	Surface mount
Dimensions L x W x H	520mm x 180mm x 135mm
Weight	3.4kg
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery	2 x Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Twin Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.8 Watts (Standby), 5.5 Watts (Max)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D160 C ₉₀ =D160

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,noBRKT
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP
8003060	PCA: DALI Node #CT10629-Ax

