



LWP2LIFE-PRO-WPPOD-HV-BLK

CLEVERTRONICS L10 IP66/67 WEATHERPROOF SURFACE MOUNT
EMERGENCY WITH TWIN LIFELIGHT PRO PODS - BLACK



PRODUCT INFORMATION	
Part Number	LWP2LIFE-PRO-WPPOD-HV-BLK
MIC	AUT01820160001
Description	L10 Optimum Lifelight Pro, High Performance, IP66/67 Surface Mounted Emergency Light with Twin LED Pods, Black
Construction	Polycarbonate
Mounting	Surface Mount
Dimensions L x W x H	520mm x 180mm x 135mm
Weight	3.4kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh (QTY 2)
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Twin Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.8 Watts (Standby), 5.5 Watts (Max)
IP Rating	IP66/67
Operating Temperature	0°C to 40°C
AS2293 Classification	Ceiling Mount: C0=D160 C90=D160 Wall Mount: C0=D160 C90=D80 C270=D125
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead, no Brkt (QTY 2)
2750353	LED:LP/L10 WP POD, Gen2, 2 LED, Sub Assy (QTY 4)
AUM01870090001 LLIFE-PRO-CKIT-HV-NP	Lifelight Pro,Control Only, L10, HV, OWC, NP (QTY 2), incl Hive nodes
8003191	PCA: RF Node CT10678-A12 Int Antenna LLPro

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.