



LWP2LIFE-PRO-WPPOD-HV

CLEVERTRONICS L10 WEATHERPROOF SURFACE MOUNT
WITH TWIN LIFELIGHT PRO PODS (ZONENETWORKS HIVE)



PRODUCT INFORMATION

| | |
|--------------------------|--|
| Part Number | LWP2LIFE-PRO-WPPOD-HV |
| MIC | AUT01820080001 |
| Description | L10 Lithium Nanophosphate Lifelight Pro, high performance, IP65 surface mounted Emergency Light with twin rotatable LED Pods |
| Construction | Polycarbonate |
| Mounting | Surface mount |
| Dimensions L x W x H | 520mm x 180mm x 135mm |
| Weight | 3.4kg |
| Operating Mode | Non-maintained |
| Testing System | Zoneworks XT HIVE (RF) |
| Battery | 4 x Lithium Nanophosphate, 3.3V 2500mAh |
| Charging Method | Intelligent current limited constant voltage |
| Lamp(s) | Twin Dual LED (Lifetime warranty on the lamp head and loom assembly) |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 0.8 Watts (Standby), 5.5 Watts (Max) |
| IP Rating | IP65 |
| Operating Temperature | 0°C to 40°C |
| AS2293 Classification | Ceiling Mount: C0=D160 C90=D160 Wall Mount: C0=D160 C90=D80 C270=D125 |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|--|---|
| 1530050 | BATTERY:L10 3.3V 2.5AH 70mm lead,noBRKT (Qty 4) |
| 2750353 | LED:LP/L10 WP POD, Gen2, 2 LED, Sub Assy (QTY 2) |
| AUM01870090001 LLIFE-PRO-CKIT-HV-NP | Lifelight Pro,Control Only, L10, HV, OWC, NP (QTY 2), incl Hive nodes |
| 8003191 | PCA: RF Node CT10678-A12 Int Antenna LLPro |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.