



LWP2LIFE-PRO-WPPOD

CLEVERTRONICS L10 WEATHERPROOF SURFACE MOUNT
WITH TWIN LIFELIGHT PRO PODS



PRODUCT INFORMATION

Part Number	LWP2LIFE-PRO-WPPOD
MIC	AUT01320520001
Description	L10 Lithium Nanophosphate Lifelight Pro, high performance, IP65 surface mounted Emergency Light with twin rotatable LED Pods, with 1.5m LSZH rear exit fly lead for plug supplied by CYP.
Construction	Polycarbonate
Mounting	Surface mount
Dimensions L x W x H	520mm x 180mm x 135mm
Weight	3.4kg
Operating Mode	Non-Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	4 x Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Twin Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	220-240V~ 50Hz
Power Consumption	0.8 Watts (Standby), 5.4 Watts (Max)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	Ceiling Mount: C0=D160 C90=D160 Wall Mount: C0=D160 C90=D80 C270=D125
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	Battery
8050205	Led
AUM01370120002	Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.