



## LWPLIFE-PRO-DALI-CM-WHT

CLEVERTRONICS L10 LIFELIGHT PRO CEILING MOUNT  
EMERGENCY LUMINAIRE, WHITE (DALI REGISTERED)



PRODUCT INFORMATION	
Part Number	LWPLIFE-PRO-DALI-CM-WHT
MIC	AUT01220510102
Description	L10 Optimum LifeLight PRO, Ceiling Mounted Emergency, White, DALI Registered
Construction	Die Cast Aluminium Body Stainless Steel Screws Clear Toughened Glass
Mounting	Ceiling Mounted
Dimensions	186mm Diameter x 289mm Height
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x 3W LED (Lifetime Warranty on the Lamp Head and Loom Assembly)
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.7W (Standby), 3W (Max)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D50 C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530230	Battery
1100869	LED Head Assembly
AUM01270240002 LLIFE-PRO-CKIT-DALI-NP	Emergency Driver
8003060	Node - DALI

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.