



LWPLIFE-PRO-FZR-HV

CLEVERTRONICS L10 LIFELIGHT PRO WEATHERPROOF
SURFACE MOUNT EMERGENCY FOR LOW TEMPERATURE APPLICATIONS



PRODUCT INFORMATION

Part Number	LWPLIFE-PRO-FZR-HV
MIC	AUT01820200001
Description	L10 Optimum Lifelight PRO, IP66/67 Weatherproof, Surface Mounted Emergency Light, for Low Temperature Applications
Construction	Polycarbonate
Mounting	Surface Mounted
Dimensions L x W x H	380mm x 190mm x 135mm
Weight	3.0kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh (x2)
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7W (Standby), 3.0W (Max)
IP Rating	IP66/67
IK Rating	IK08
Operating Temperature	-25°C to 40°C
AS2293 Classification	C0=D50 C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead, Brkt (2)
1100869	Lifelight Pro Head Assembly, Ld:280mm,Rnd,LT,Gen 2
AUM01870090001 LLIFE-PRO-CKIT-HV-NP	Lifelight Pro,Control Only, L10, HV, OWC, NP (incl. Hive node)
8003191	PCA: RF Node CT10678-A12 Int Antenna LLPro

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order