



# LWPLIFE-PRO-FZR

CLEVERTRONICS L10 LIFELIGHT PRO WEATHERPROOF  
SURFACE MOUNT EMERGENCY FOR LOW TEMPERATURE APPLICATIONS



## PRODUCT INFORMATION

Part Number	LWPLIFE-PRO-FZR
MIC	AUT01320020001
Description	L10 Optimum Lifelight PRO, IP66/67 Weatherproof, Surface Mounted Emergency Light for Low Temperature Applications
Construction	Polycarbonate
Mounting	Surface Mounted
Dimensions L x W x H	380mm x 190mm x 135mm
Weight	3.0kg
Operating Mode	Non-maintained
Testing System	Manual testing
Battery	Lithium Nanophosphate, 3.3V 5000mAh (x2)
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4W (Standby), 2.7W (Max)
IP Rating	IP66/67
IK Rating	IK08
Operating Temperature	-25°C to 40°C
AS2293 Classification	C <sub>0</sub> =D50 C <sub>90</sub> =D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

## REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead, Brkt (QTY 2)
1100869	Lifelight Pro Head Assembly, Ld:280mm,Rnd,LT,Gen 2
AUM01370120001 LLIFE-PRO-CKIT-NP	Lifelight Pro,Control Only,Batten,L10, CTP, OWC,NP

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order