



LCFLED-TH-HV-RL

CLEVERTRONICS L10 CLEVERFIT EXIT, THEATRE
(ZONWORKS XT HIVE)



PRODUCT INFORMATION

Part Number	LCFLED-TH-HV-RL
MIC	AUA01860160001
Description	L10 Optimum LED Cleverfit Emergency Exit with Theatre Mask
Construction	ABS Body and Diffuser with Clear Polycarbonate Tamper Proof Cover
Mounting	Wall or Ceiling Mounted, Single Sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre Mask, Running Man, Arrow Left
Lamp(s)	6 x LED, 100,000Hrs
Operating Voltage	240V AC: 50Hz
Power Consumption	2.7 Watts (Standby) 4.5 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	Battery
8002430	Emergency LED Panel
8002320	Driver
8003191	Emergency Node - HIVE

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.